

9.16

9.16 A smooth, flat plate of length  $\ell = 6 \text{ m}$  and width  $b = 4 \text{ m}$  is placed in water with an upstream velocity of  $U = 0.5 \text{ m/s}$ . Determine the boundary layer thickness and the wall shear stress at the center and the trailing edge of the plate. Assume a laminar boundary layer.

$$\delta = 5 \sqrt{\frac{Vx}{U}} = 5 \sqrt{\frac{(1.12 \times 10^{-6} \frac{m^2}{s}) X}{0.5 \frac{m}{s}}} = 7.48 \times 10^{-3} \sqrt{X} \text{ m, where } X \sim m$$

and

$$\tau_w = 0.332 U^{3/2} \sqrt{\frac{\rho \mu}{X}} = 0.332 (0.5 \frac{m}{s})^{3/2} \sqrt{\frac{(999 \frac{kg}{m^3})(1.12 \times 10^{-3} \frac{N \cdot s}{m^2})}{X}}$$
$$= \frac{0.124}{\sqrt{X}} \frac{N}{m^2}, \text{ where } X \sim m$$

Thus, at  $X = 3 \text{ m}$   $\delta = 7.48 \times 10^{-3} \sqrt{3} = \underline{\underline{0.0130 \text{ m}}}$

$$\tau_w = \frac{0.124}{\sqrt{3}} = \underline{\underline{0.0716 \frac{N}{m^2}}}$$

while at  $X = 6 \text{ m}$   $\delta = 7.48 \times 10^{-3} \sqrt{6} = \underline{\underline{0.0183 \text{ m}}}$

$$\tau_w = \frac{0.124}{\sqrt{6}} = \underline{\underline{0.0506 \frac{N}{m^2}}}$$