4.60

4.60 Water flows through the 2-m-wide rectangular channel shown in Fig. P4.60 with a uniform velocity of 3 m/s. (a) Directly integrate Eq. 4.16 with b=1 to determine the mass flowrate (kg/s) across section CD of the control volume. (b) Repeat part (a) with $b=1/\rho$, where ρ is the density. Explain the physical interpretation of the answer to part (b).





FIGURE P4.60

a)
$$\dot{B}_{out} = \int_{cs_{out}} \rho b \ \vec{V} \cdot \hat{n} \ dA$$

With b = l and $\vec{V} \cdot \hat{n} = V \cos \theta$ this becomes

$$\dot{B}_{out} = \int_{CD} PV \cos\theta \, dA = PV \cos\theta \int_{CD} dA$$

= $\rho V \cos \theta A_{cD}$, where $A_{cD} = l (2m)$ = $\left(\frac{0.5 m}{\cos \theta}\right) (2m)$ = $\left(\frac{1}{\cos \theta}\right) m^2$



(1)

Thus, with
$$V=3m/s$$
.
$$\dot{B}_{out} = (3\frac{m}{s})\cos\theta \left(\frac{1}{\cos\theta}\right)m^2(999\frac{kq}{m^3}) = 3000\frac{kq}{s}$$

b) With b = 1/p Eq. (1) becomes

$$\dot{B}_{out} = \int_{CD} \vec{V} \cdot \hat{n} dA = \int_{CD} V \cos\theta dA = V \cos\theta A_{CD}$$

$$= (3 \frac{m}{s}) \cos\theta \left(\frac{1}{\cos\theta}\right) m^2 = 3.00 \frac{m^3}{s}$$

With $b = 1/\rho = \frac{1}{(\frac{mass}{vol})} = \frac{vol}{mass}$ it follows that "B = volume" (i.e., $b = \frac{B}{mass}$) so that $\int \vec{V} \cdot \hat{n} dA = \vec{B}_{out}$ represents the volume flowrate (m³/s) from the control volume.