5.117

5. 117 Water is supplied at 150 ft³/s and 60 psi to a hydraulic turbine through a 3-ft inside diameter inlet pipe as indicated in Fig. P5.117. The turbine discharge pipe has a 4-ft inside diameter. The static pressure at section (2), 10 ft below the turbine inlet, is 10-in. Hg vacuum. If the turbine develops 2500 hp, determine the power lost between sections (1) and (2).




FIGURE P5.117

For flow between sections (1) and (2), Eq. 5.82 leads to power loss = $\rho \mathcal{R} \left[\frac{P_1 - P_2}{\rho} \right] + g(\overline{z}_1 - \overline{z}_2) + \left(\frac{V_1^2 - V_2}{2} \right)^2 - \widetilde{W}_{shaft}$ (1)

From given data

$$P_{2} = \frac{(-10 \text{ in. Hg})(13.6)(1.94 \text{ slugs})(32.2 \frac{ft}{ft})}{(12 \frac{in.}{ft})} = -\frac{708 \frac{16}{ft^{2}}}{ft^{2}}$$

Also

$$V_1 = \frac{Q}{A_1} = \frac{Q}{\pi D_1^2} = \frac{(4)(150 \frac{ft^3}{5})}{\pi (3ft)^2} = 21.22 \frac{ft}{5}$$

From conservation of mass (Eq. 5.13)

$$V_2 = V_1 \frac{A_1}{A_2} = V_1 \frac{D_1^2}{D_2^2} = (21.22 \frac{ft}{s}) \frac{(3ft)^2}{(4ft)^2} = 11.94 \frac{ft}{s}$$

From Eq. 1

power loss =
$$\frac{(1.94 \text{ slugs})(150 \text{ ft}^3)}{(550 \text{ ft} \cdot 1b)} \frac{(60 \text{ lb})(144 \text{ in.}^2)}{(1.94 \text{ slugs})} + (708 \frac{\text{lb}}{\text{ft}^2})}{(1.94 \text{ slugs})}$$

+ $(32.2 \frac{\text{ft}}{\text{s}^2})(10 \text{ ft})(\frac{1}{\text{slug. ft}}) + (21.22 \frac{\text{ft}}{\text{s}})^2 - (11.94 \frac{\text{ft}}{\text{slug.ft}})$
- $2500hp$

Or