4.72 Water flows through the 2-m-wide rectangular channel shown in Fig. P4.72 with a uniform velocity of 3 m/s. (a) Directly integrate Eq. 4.16 with b=1 to determine the mass flowrate (kg/s) across section CD of the control volume. (b) Repeat part (a) with $b=1/\rho$, where ρ is the density. Explain the physical interpretation of the answer to part (b).




FIGURE P4.72

(1)

a)
$$\dot{B}_{out} = \int_{csout} \rho b \, \vec{V} \cdot \hat{n} \, dA$$

With $b = l$ and $\vec{V} \cdot \hat{n} = V \cos \theta$ this becomes $\int_{c}^{l} \dot{B}_{out} = \int_{cp} \rho V \cos \theta \, dA = \rho V \cos \theta \int_{cp} dA$
 $= \rho V \cos \theta \, A_{cp}$, where $A_{cp} = L(2m)$
 $= (\frac{0.5 \, m}{\cos \theta})(2m)$
 $= (\frac{1}{\cos \theta}) m^2$

Thus, with
$$V=3m/s$$
,
$$\dot{B}_{out} = \left(3\frac{m}{s}\right)\cos\theta\left(\frac{1}{\cos\theta}\right)m^2\left(999\frac{kq}{m^3}\right) = 3000\frac{kq}{s}$$

b) With
$$b = 1/\rho$$
 Eq. (1) becomes
$$\dot{B}_{out} = \int \vec{V} \cdot \hat{n} \, dA = \int V \cos\theta \, dA = V \cos\theta \, A_{cD} \\
= \left(3 \frac{m}{s}\right) \cos\theta \, \left(\frac{1}{\cos\theta}\right) m^2 = 3.00 \frac{m^3}{s}$$

With $b = 1/\rho = \frac{1}{(\frac{mass}{vol})} = \frac{vol}{mass}$ it follows that "B = volume" (i.e., $b = \frac{B}{mass}$) so that $\int \vec{V} \cdot \hat{n} dA = \vec{B}_{out}$ represents the volume flowrate (m³/s) from the control volume.