


8.78

Q.78 As shown in Video V3.5 and Fig. P8.78 water "bubbles" up 3 in. above the exit of the vertical pipe attached to three horizontal pipe segments. The total length of the 0.75-in.-diameter galvanized iron pipe between point (1) and the exit is 21 in. Determine the pressure needed at point (1) to produce this flow.



■ FIGURE P8.78

$$\frac{p_1}{g} + \frac{V_1^2}{2g} + z_1 - h_L = \frac{p_2}{g} + \frac{V_2^2}{2g} + z_2$$

where $z_1 = 0$, $p_2 = 0$, $V_2 = 0$. Thus,

$$(1) \quad \frac{p_1}{g} = z_2 + h_L - \frac{V_1^2}{2g} \text{ where } V_1 = V_3 = V$$

With no head loss from (3) to (2) and $p_2 = p_3 = V_2 = 0$ we obtain

$$\frac{V_3^2}{2g} + z_3 = z_2, \text{ or } V_3 = \sqrt{2g(z_2 - z_3)} = \sqrt{2(32.2 \frac{\text{ft}}{\text{s}^2})(\frac{3}{12} \text{ft})} = 4.01 \text{ ft/s}$$

Thus,

$$Re = \frac{VD}{\nu} = \frac{V_3 D}{\nu} = \frac{4.01 \frac{\text{ft}}{\text{s}} (\frac{0.75}{12} \text{ft})}{1.21 \times 10^{-5} \frac{\text{ft}^2}{\text{s}}} = 2.07 \times 10^4$$

and

$$\frac{E}{D} = \frac{0.0005 \text{ ft}}{\left(\frac{0.75}{12}\right) \text{ ft}} = 0.008 \quad (\text{see Table 8.1}), \text{ so that (see Fig. 8.20)}$$

$$f = 0.039$$

$$\text{Also, } h_L = f \frac{L}{D} \frac{V^2}{2g} + \sum K_L \frac{V^2}{2g} \text{ where } \sum K_L = 3(1.5) = 4.5$$

Hence, Eq. (1) becomes

$$\frac{p_1}{g} = z_2 + [f \frac{L}{D} + \sum K_L] \frac{V^2}{2g} - \frac{V_1^2}{2g} \text{ where } V_1 = V$$

or

$$\frac{p_1}{g} = \frac{z}{12} \text{ ft} + \left[0.039 \frac{21 \text{ in.}}{0.75 \text{ in.}} + 4.5 + 1 \right] \frac{(4.01 \frac{\text{ft}}{\text{s}})^2}{2(32.2 \frac{\text{ft}}{\text{s}^2})} = (0.583 + 1.147) + 1.73 \text{ ft}$$

Thus,

$$p_1 = (62.4 \frac{\text{lbf}}{\text{in}^2})(1.73 \text{ ft}) = 108 \frac{\text{lbf}}{\text{in}^2} = \underline{0.750 \text{ psi}}$$